

## SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING																			
<b>1.1</b>	<b>Product identifier</b>																		
	<table> <tr> <td><b>Substance name</b></td> <td>Natural gas, Biogas</td> </tr> <tr> <td><b>CAS-no</b></td> <td>8006-14-2</td> </tr> <tr> <td><b>Tunnuskoodi</b></td> <td>Natural gas</td> </tr> <tr> <td><b>Reach registration number</b></td> <td>N/A; Natural gas is exempted from REACH registration (Annex V)</td> </tr> </table>	<b>Substance name</b>	Natural gas, Biogas	<b>CAS-no</b>	8006-14-2	<b>Tunnuskoodi</b>	Natural gas	<b>Reach registration number</b>	N/A; Natural gas is exempted from REACH registration (Annex V)										
<b>Substance name</b>	Natural gas, Biogas																		
<b>CAS-no</b>	8006-14-2																		
<b>Tunnuskoodi</b>	Natural gas																		
<b>Reach registration number</b>	N/A; Natural gas is exempted from REACH registration (Annex V)																		
<b>1.2</b>	<b>Relevant identified uses of the substance or mixture and uses advised against</b>																		
	<table> <tr> <td><b>Relevant identified uses</b></td> <td>Fuel. Engine fuel. Raw material for chemical industry. Pressurized natural gas. May also be called CNG Pressurized natural gas, when P &gt; 55 bar.</td> </tr> <tr> <td><b>NACE code</b></td> <td>D35 Electricity, gas, steam and air conditioning supply C20 Manufacture of chemicals and chemical products</td> </tr> <tr> <td><b>Purpose of use code</b></td> <td>55 Other chemicals</td> </tr> <tr> <td><b>This chemical may be used for common consumption</b></td> <td>X</td> </tr> <tr> <td><b>This chemical is only used for common consumption</b></td> <td>This chemical is not used for common consumption.</td> </tr> </table>	<b>Relevant identified uses</b>	Fuel. Engine fuel. Raw material for chemical industry. Pressurized natural gas. May also be called CNG Pressurized natural gas, when P > 55 bar.	<b>NACE code</b>	D35 Electricity, gas, steam and air conditioning supply C20 Manufacture of chemicals and chemical products	<b>Purpose of use code</b>	55 Other chemicals	<b>This chemical may be used for common consumption</b>	X	<b>This chemical is only used for common consumption</b>	This chemical is not used for common consumption.								
<b>Relevant identified uses</b>	Fuel. Engine fuel. Raw material for chemical industry. Pressurized natural gas. May also be called CNG Pressurized natural gas, when P > 55 bar.																		
<b>NACE code</b>	D35 Electricity, gas, steam and air conditioning supply C20 Manufacture of chemicals and chemical products																		
<b>Purpose of use code</b>	55 Other chemicals																		
<b>This chemical may be used for common consumption</b>	X																		
<b>This chemical is only used for common consumption</b>	This chemical is not used for common consumption.																		
<b>1.3</b>	<b>Details of the Supplier of the Safety Data Sheet</b>																		
	<table> <tr> <td colspan="2"><b>Manufacturer, importer or other trader</b></td> </tr> <tr> <td><b>Trader acting in Finland</b></td> <td>Gasum Oy</td> </tr> <tr> <td><b>Street address</b></td> <td>Revontulenpuisto 2 C</td> </tr> <tr> <td><b>Postcode and place</b></td> <td>02100 ESPOO</td> </tr> <tr> <td><b>P.O. Box</b></td> <td>P.O. Box 21</td> </tr> <tr> <td><b>Postcode and place</b></td> <td>02151 ESPOO</td> </tr> <tr> <td><b>Telephone number</b></td> <td>0800 122 722</td> </tr> <tr> <td><b>E-mail address</b></td> <td>asiakaspalvelu@gasum.com</td> </tr> <tr> <td><b>Business ID</b></td> <td>0969819-3</td> </tr> </table>	<b>Manufacturer, importer or other trader</b>		<b>Trader acting in Finland</b>	Gasum Oy	<b>Street address</b>	Revontulenpuisto 2 C	<b>Postcode and place</b>	02100 ESPOO	<b>P.O. Box</b>	P.O. Box 21	<b>Postcode and place</b>	02151 ESPOO	<b>Telephone number</b>	0800 122 722	<b>E-mail address</b>	asiakaspalvelu@gasum.com	<b>Business ID</b>	0969819-3
<b>Manufacturer, importer or other trader</b>																			
<b>Trader acting in Finland</b>	Gasum Oy																		
<b>Street address</b>	Revontulenpuisto 2 C																		
<b>Postcode and place</b>	02100 ESPOO																		
<b>P.O. Box</b>	P.O. Box 21																		
<b>Postcode and place</b>	02151 ESPOO																		
<b>Telephone number</b>	0800 122 722																		
<b>E-mail address</b>	asiakaspalvelu@gasum.com																		
<b>Business ID</b>	0969819-3																		
<b>1.4</b>	<b>Emergency number</b>																		
	<p>Poison Information Centre:            Finland: 09 471 977            Sweden: 010-456 6700            Norway: +47 22 59 13 00</p>																		
SECTION 2. HAZARDS IDENTIFICATION																			
<b>2.1</b>	<b>Classification of the substance or mixture</b>																		

### EY (No) 1272/2008 CLP classification:

Flam. Gas 1 H220	Extremely flammable gas
Press. Gas (Comp.) H280	Contains gas under pressure; may explode if heated.

## 2.2 Label elements

Hazard pictograms:



GHS02, GHS04  
Signal word: Danger

**Hazard statements:**

Flam. Gas 1 H220	Extremely flammable gas
Press. Gas (Comp.) H280	Contains gas under pressure; may explode if heated.

**Precautionary statements:**

**Precaution**

P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
------	--

**Response precautionary statement:**

P377	Leaking gas fire: Do not extinguish unless leak can be stopped safely.
P381	Eliminate all ignition sources if safe to do so.

**Storage:**

P403	Store in a well-ventilated place.
P410 + P403	Protect from sunlight. Store in a well-ventilated place.

## 2.3 Other hazards

Contains at least 85 mol-% of methane. Natural gas may be odorized.

Safety hazards: Natural gas is lighter than air and together with air forms a flammable/explosive mixture of air and gas.

Health hazards: In high concentrations, the inhalation of natural gas may cause drowsiness and possibly headache, nausea or dizziness. High concentrations of gas can displace oxygen in the air. This results in a lack of oxygen, which may cause suffocation if prolonged. If it evaporates quickly, pressurized natural gas may cause freezing injuries.

PBT/vPvB- properties has not been defined.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

Substance name	CAS-, EY- number and Reg. No.	Content
Natural gas	8006-14-2	c. 100 %

3.2 Mixture				
Substance name	CAS-, EY- number and Reg. No.	REACH-reg. No.	Content (%)	Classification
Not applied; Substance	Not applied; Substance	Not applied; Substance	Not applied; Substance	Not applied; Substance

## SECTION 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

#### Inhalation:

A person who has inhaled gas shall be moved to fresh air, kept warm and at rest. Give oxygen or mouth-to-mouth ventilation, if necessary. If the exposure has been remarkable, seek medical attention.

#### Swallowed:

The substance is a gas and swallowing it is not a likely way to be exposed.

#### Skin contact:

Warm up the skin immediately by flushing with plenty of water. If the exposure has been remarkable, seek medical attention.

#### Eye contact:

Flush immediately with plenty of water for at least 15 minutes. Keep flushing until the patient gets medical attention (an eye specialist is preferred).

### 4.2 Most important symptoms and effects, both acute and delayed

In high concentrations, breathing of natural gas may cause drowsiness, possibly headache, nausea or dizziness. High concentrations of gas can displace oxygen in the air. This results in a lack of oxygen, which may cause suffocation, if prolonged.

### 4.3 Indication of any immediate medical attention and special treatment needed

Medical measures according to symptoms. Give oxygen or mouth-to-mouth ventilation, if necessary.

## SECTION 5. FIREFIGHTING MEASURES

### 5.1 Extinguishing media

Leave fire-fighting measures to professional fire-fighters. Call the common emergency number 112. Turn off the check valve(s) on the natural gas pipe that leads to the leakage if safe to do so.

### 5.2 Special hazards arising from the substance or mixture

Together with air, natural gas forms a flammable/explosive mixture. It poses the danger of explosion when the gas accumulates in closed spaces. There is the danger of explosion when the pressure rises if the gas pipework increases in heat due to fire.

### 5.3 Advice for firefighters

Protective equipment: complete protective clothing and self-contained breathing apparatus.

Stop access to leakage by turning off the check valve(s) on the natural gas pipe that leads to the leakage if safe to do so. If this valve cannot be turned off and the fire does not pose a danger to the surroundings, let the fire burn out on its own. Use water spray from a safe distance to cool nearby gas pipework and devices.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

If possible, turn off the check valve(s) on the natural gas pipe that leads to the leakage.

Eliminate the danger of fire and explosion by isolating the area from ignition sources (e.g. heat, sparks, open fire, hot surfaces) and by inhibiting the accumulation of gas in closed spaces.

Evacuate people from the dangerous area to a spot above wind. It may be possible to control the evaporation of the gas with water sprays, if necessary. Monitor the dangerous area with gas detectors.

In case of an accident, a notice shall immediately be given to the emergency centre: general emergency number 112. Suitable protective equipment must be worn during all measures.

## 6.2 Environmental precautions

No particular safety measures

## 6.3 Methods and material for containment and clean-up

Controlled evaporation or incineration. The danger posed by fire and explosion as well as health risk should be observed. The space needs to be ventilated well.

## 6.4 Reference to other sections

Mentioned in section 7, 8.

## SECTION 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Protect from heat, sunlight, hot surfaces, sparks, open fire and other ignition sources. No smoking. Keep isolated from ignition sources. Use protective measures (e.g. ground connections) to inhibit sparking due to induced electricity. Make sure the room is sufficiently ventilated when handling the product. Make sure there are no leakages due to open valves or leaking junctions.

### 7.2 Conditions for safe storage, including incompatibilities

Use special containers or pipework suitable for extremely flammable gases (natural gas). Protect from heat, sunlight, hot surfaces, sparks, open fire and other ignition sources. No smoking. Keep isolated from ignition sources. No smoking. Keep isolated from ignition sources. Use protective measures (e.g. ground connections) to inhibit sparking due to induced electricity. Adequate ventilation should be provided. Before conducting any cleaning, inspection or other service and maintenance procedures, make sure this is safe.

### 7.3 Specific end use(s)

No specific end use.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

#### HTP-values

No value determined (CAS 8006-14-2) according to decree 1214/2016 by Ministry of Social affairs and Health

#### Other limit values

N/D

#### DNEL-values

N/D

#### PNEC-values

N/D

### 8.2 Exposure controls

#### Appropriate engineering controls

Make sure the room is sufficiently ventilated when handling the product. Specific instructions need to be followed when cleaning the containers and pipework (risk of displacement of oxygen). Choose control measures on the basis of risk assessment with consideration also given to the local conditions.

#### Eye/face protection

If necessary, a face shield and safety goggles that fit tightly.

#### Skin protection

No specific need. If necessary, use anti-static and fire retardant clothing.

#### Hand protection

Use cold-resistant gloves when handling a liquefied product.

#### Respiratory protection

Use pressure pneumatic appliance

#### Thermal dangers

Use cold-resistant gloves when handling a liquefied product.

#### Environmental exposure controls

No specific need.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Colourless gas
<b>Odour</b>	Weak hydrocarbon odour
<b>Odour threshold</b>	N/D
<b>pH</b>	N/D
<b>Melting point / freezing point</b>	- 182 °C (methane) (Melting point)
<b>Initial boiling point and boiling range</b>	- 162 °C (methane)
<b>Flash point</b>	- 188 °C (methane)
<b>Evaporation rate</b>	N/D
<b>Flammability (solid, gas)</b>	N/D
<b>Lower and upper explosive limit</b>	Lower: 5 til-% (flammability limit) Upper: 15 til-% (flammability limit)
<b>Vapour pressure</b>	c. 150 kPa (20 °C) (water = 2,3 kPa)
<b>Vapour density</b>	N/D
<b>Relative density</b>	0,56 (air = 1)
<b>Solubility(ies)</b>	Water solubility: poorly soluble (24 mg/l, methane) Liposolubility (oil solvent, individualized): N/A
<b>Partition coefficient: n-octanol/water</b>	N/D
<b>Auto-ignition temperature</b>	537 °C (methane)
<b>Decomposition temperature</b>	N/D
<b>Viscosity</b>	N/D
<b>Explosive properties</b>	Natural gas together with air forms a flammable/explosive mixture of air and gas. May explode if heated.
<b>Oxidising properties</b>	N/D

### 9.2 Other information

Density of gas = 0,73 kg/m<sup>3</sup>

Density of liquid at boiling temperature:: 0,42 kg/l (methane)

Henry's law constant = 0,6 atm·m<sup>3</sup>/mol 1 ppm = 0,67 mg/m<sup>3</sup> (methane), 1 mg/m<sup>3</sup> = 1,50 ppm (methane).

## SECTION 10. STABILITY AND REACTIVITY

### 10.1 Reactivity

Not self-reactive.

### 10.2 Chemical stability

Stable under normal conditions

### 10.3 Possibility of hazardous reactions

No hazardous reactions

### 10.4 Conditions to avoid

Danger of ignition; avoid heat, sparks, sunlight and ignition sources. May form flammable mixtures together with air.

### 10.5 Incompatible materials

Water (may form solid hydrates under high pressure and at low temperature)

### 10.6 Hazardous decomposition products

Carbon monoxide

## SECTION 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

**Acute toxicity**

N/D

**Skin corrosion/irritation**

The gas does not irritate skin.

**Serious eye damage/irritation**

The gas does not irritate eyes.

**Airways or skin sensitisation**

The gas does not irritate airways or skin.

**Germ cell mutagenicity**

N/D

**Carcinogenicity**

N/D

**Reproductive toxicity**

N/D

**Specific target organ toxicity (STOT- single or repeated exposure)**

Large amounts of steam may cause unconsciousness. When the liquid evaporates quickly, it can cause freezing injuries. Product ingredients may be absorbed in the body when aspirated.

**Aspiration hazard**

N/D

**Other information**

No other information concerning toxicity.

## SECTION 12. ECOLOGICAL INFORMATION

### 12.1 Toxicity

Aquatic toxicity: Gaseous substance which dissolves sparsely to water.

Toxicity to other organisms: N/D

### 12.2 Persistence and degradability

Extremely slow degradability by atmospheric chemistry (estimated half-life of methane is 220 days)

### 12.3 Bioaccumulative potential

N/D

### 12.4 Mobility in soil

Liquefied product evaporates quickly into the air, where its degradability is extremely slow.

### 12.5 Results of PBT and vPvB assessment

N/D

### 12.6 Other adverse effects

N/D

## SECTION 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Incineration requires special treatment in accordance with the local regulations, due to the high pressure of the compressed gas.

## SECTION 14. TRANSPORT INFORMATION

### 14.1 UN number

UN 1971

### 14.2 UN proper shipping name

UN 1971 NATURAL GAS, COMPRESSED, with high methane content

### 14.3 Transport hazard class

#### Land transports

Transport class: 2

Danger identification number: 23

ADR/RID hazardous material label 2.1

#### Sea transport

IMDG class: 2.1

#### Air transport

Not transported by air

### 14.4 Packing group

2.1 F P200 package, packaging group number 1F

### 14.5 Environmental hazards

No specific environmental hazards

### 14.6 Special precautions for user

Mentioned in section 7 – 8

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No specific statements.

## SECTION 15. REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Exhaustive legislation for natural gas pipework and gas appliances has been drawn up in Finland. The most central of all regulations is the government decree on the safe handling of natural gas (551/2009), which is based on the Act on Safe Handling and Storage of Dangerous Chemicals and Explosives (390/2005).

Seveso III-directive (2012/18/EU) applies to natural gas.

### 15.2 Chemical Safety Assessment

A chemical safety assessment has not been performed.

## SECTION 16. OTHER INFORMATION

### Indication of changes

Removed 67/548/ETY classifications, new form overlay and revised the hazard statements.

### Lyhenteiden selitykset

DNEL	The derived no-effect level
HTP	Harmful known concentrations
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
vPvB	Very persistent and very bioaccumulative

### Sources of data

Gasum Natural gas/Biogas Safety data sheet revised 13.6.2012.

### Classification and procedure used to derive the classification for mixtures

CLP-regulation (EY N:o 1272/2008).

## List of R and S statements or/and danger and hazard statements

### Hazard statements

H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated.

### Precautionary statements

P210	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P377	Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381	Eliminate all ignition sources if safe to do so.
P403	Store in a well-ventilated place.
P410 + P403	Protect from sunlight. Store in a well-ventilated place.

### Training advice

Review sections 4 – 8 and show the location of necessary safety devices.